

TEEKAY AXIFLEX

HINGED COUPLINGS

- Fully opening permanent pipe coupling
- Installation in areas of limited access
- Suitable for most pipe materials
- No loose parts
- No special pipe preparation
- Installed in minutes
- New installations or retro fit
- Design Patent





- Sizes 80mm 1200mm NB
- Can be made to suit any pipe OD
- Up to PN16 pressure rating
- EPDM or NBR gaskets
- Casings stainless or coated steel
- Alloy or stainless screws
- ISO 9001

Another innovative technical solution from TEEKAY Couplings.

Use materials of the highest quality – save time and money on installation.

Our service and delivery are legendary.

AXIFLEX HC "MORE VALUE - LESS COST!"


AXIFLEX HINGED COUPLINGS


DIMENSIONAL DETAILS



D1 PIPE OUTSIDE DIAMETER	PIPE NOMINAL BORE	W1 COUPLING WIDTH				W2 GAP BETWEEN	D2 COUPLING	D3 OVERALL COUPLING	NO. OF SCREWS	APPROX WEIGHT	TOLERANCE ON PIPE O.D.
		110mm	140mm	210mm	310mm	SEALING LIPS	O.D. = (D1 + D2)	O.D. = (D1 + D3)		KGS	+/-
COUPLINGS CAN BE D TO SUIT ANY PIPE R WITHIN THIS RANGE	75	✓				67	22	66	2/4	3	2
	100	✓				67	22	66	2/4	3	2
	150	√	√			67/80	22/28	66/88	2/4	4/5	2.5/2.5
	200	✓	✓	✓		67/80/120	22/28/42	66/88/102	2/2/2	4/6/10	3/3/3
	250	1	✓	✓		67/80/120	22/28/42	66/88/102	2/2/2	5/6/10	3/3/3
	300	✓	✓	1	✓	67/80/120/220	22/28/42/42	66/88/1 <mark>02/102</mark>	2/2/2/4	5/7/11/ <mark>21</mark>	3/4/4/4
	350		\checkmark	√	√	80/120/220	28/42/42	88/102/102	2/3/4	8/13/22	4/4/4
	400		✓	✓	✓	80/120/220	28/42/42	88/ <mark>102/102</mark>	2/3/4	9/15/24	4/4/4
	450		\checkmark	✓	✓	80/120/220	28/42/42	88/102/102	2/3/4	11/16/26	4/4/4
	500		✓	✓	✓	80/120/220	28/42/42	88/ <mark>102/102</mark>	2/3/4	11/18/31	4/4/4
TEEKAY REPAIR CO MANUFACTURED OUTSIDE DIAMETER	600		✓	✓	✓	80/120/220	28/42/42	88/102/102	2/3/4	13/20/35	4/5/5
	700		✓	✓	✓	80/120/220	28/42/42	88/ <mark>102/102</mark>	2/3/4	14/25/39	4/5/5
	800		✓	✓	✓	80/120/220	28/42/42	88/102/102	2/3/4	16/27/43	4/5/5
	900		✓	✓	✓	80/120/220	28/42/42	88/102/102	2/3/4	18/30/46	4/5/5
	1000		✓	✓	✓	80/120/220	28/42/42	88/102/102	2/3/4	19/33/50	4/5/5
	1100		✓	✓	✓	80/120/220	28/42/42	88/102/102	2/3/4	20/41/54	4/5/5
	1200		✓	1	✓	80/120/220	28/42/42	88/ <mark>102/102</mark>	2/3/4	22/44/58	4/5/5

LARGER DIAMETERS ARE AVAILABLE ON REQUEST







The coupling is delivered ready to install and with no loose parts.



Axiflex HC Couplings were retro-fitted to these new GRP pipes to allow thermal and axial movement.



This large diameter water main was repaired in minutes without shutting down the line.



Teekay Axiflex HC is designed to be a **permanent** pipeline solution



126 couplings were installed in two nine hour nightshifts without disruption or shutdown to the lines.



AXIFLEX HC MATERIAL SELECTION GUIDE

Type	I	II	IV	V	VI
Casing	AISI 304	AISI 304	AISI 316L	*Coated	*Coated
	DIN 1.4301	DIN 1.4301	DIN 1.4404	High Strength	High Strength
				_	Steel
				Steel	
Fasteners	Alloy Steel	AISI 316L	AISI 316L	Alloy Steel	AISI 316L
	Zinc + PTFE	DIN 1.4404	DIN 1.4404	Zinc Coated	DIN 1.4404
	Coated				
Gasket	EPDM/NBR/	EPDM/NBR/	EPDM/NBR/	EPDM/NBR/	EPDM/NBR/
	Viton	Viton	Viton	Viton	Viton

^{*} Galvanized, Rilsan, PVC or Epoxy (Scotchkote)

Ordering Information:

	Quantity	Model	Type	Gasket	Pipe OD
Example:	12	Axiflex HC	V Rilsan	EPDM	323.9mm