

REPAIR COUPLING

Product Information

TEEKAY AXIFLEX COUPLING

Casing Standard Type 1 Stainless Steel AISI304
Internal Components : Stainless Steel AISI304
Lock Parts : Fasteners High Tensile Steel, Zinc & PTFE



EPDM Sealing Sleeves -40°C to +100°C

Is suitable for most effluents and is available in WRC approved compounds for potable water. Has outstanding resistance to ageing, weathering, ozone, oxygen and many chemicals.

NBR Sealing Sleeves -30°C to +80°C

Is suitable for use with petroleum products and gas as well as general services such as water, sewage etc.

OD mm	OD +/- Tolerance	Length mm	Nominal P Bar
48.3	1	85	16
60.3	1.5	87	16
76.1	1.5	87	16
88.9	1.5	87	16
114.3	2	87	16
139.7	2	112	16
168.3	2	112	16
219.1	2	112	16

TEEKAY AXIREP COUPLING

Casing Standard Type 1 Stainless Steel AISI304
Internal Components : Stainless Steel AISI304
Lock Parts : Fasteners High Tensile Steel, Zinc & PTFE



EPDM Sealing Sleeves -40°C to +100°C

Is suitable for most effluents and is available in WRC approved compounds for potable water. Has outstanding resistance to ageing, weathering, ozone, oxygen and many chemicals.

NBR Sealing Sleeves -30°C to +80°C

Is suitable for use with petroleum products and gas as well as general services such as water, sewage etc.

OD mm	OD +/- Tolerance	Length mm	Nominal P Bar
48.3	1	86	16
60.3	1.5	87	16
76.1	1.5	111	16
88.9	1.5	113	16
114.3	2	114	16
139.7	2	114	16
168.3	2	114	16
219.1	2	115	16

TEEKAY AXILOCK COUPLING

Casing Standard Type 1 Stainless Steel AISI304
Internal Components : Stainless Steel AISI304
Lock Parts : Fasteners High Tensile Steel, Zinc & PTFE coated



EPDM Sealing Sleeves -40°C to +100°C

Is suitable for most effluents and is available in WRC approved compounds for potable water. Has outstanding resistance to ageing, weathering, ozone, oxygen and many chemicals.

NBR Sealing Sleeves -30°C to +80°C

Is suitable for use with petroleum products and gas as well as general services such as water, sewage etc.

OD mm	OD +/- Tolerance	Length mm	Nominal P Bar
48.3	1	65	16
60.3	1.5	85	16
76.1	1.5	85	16
88.9	1.5	85	16
114.3	2	85	16
139.7	2	110	16
168.3	2	110	13
219.1	2	110	6

MAXIDAPTOR

Flange adaptors designed to accommodate plain ended pipes with different outside diameters. For use on steel, ductile iron, cast iron, PVCu and asbestos cement.



Finish: Black Rilsan Coat
Nuts & Bolts: Rilsan Coat
Gasket: E.P.D.M ("E" Grade)
Options: British Gas LC6 approved gaskets

Product Code	Description	Clamp Size
10480050	Maxidaptor (range 59.2- 72mm) NP16/DE	50mm
10480065	Maxidaptor (range 72.2-85mm) NP16/DE	65mm
10480080	Maxidaptor (range 88.1-102.4mm) NP16/DE	80mm
10480100	Maxidaptor (range 109.6-127.8mm) NP16/DE	100mm
10480125	Maxidaptor (range 132.2-146mm) NP16/DE	125mm
10480150	Maxidaptor (range 159.2-181.6mm) NP16/DE	150mm
10480200	Maxidaptor (range 218.1-235mm) NP16/DE	200mm

HANDBAND

A range of small bore stainless steel repair clamps.



Nuts & Bolts: Mild Steel
Gasket: E.P.D.M ("E" Grade)
Options: British Gas LC6 approved gaskets

Product Code	Description	Clamp Size
10500015	Handiband (15-22mm)	15x75mm
10500020	Handiband (26-30mm)	20x75mm
10500025	Handiband (33-37mm)	25x75mm
10500032	Handiband (42-45mm)	32x75mm
10500040	Handiband (48-54mm)	40x75mm
10500050	Handiband (60-64mm)	50x75mm

EASI CLAMP / EASITAP

A range of high strength repair clamps for use on steel, ductile iron, cast iron PVCu (up to 200mm/8") and PE pipes (up to 220/8"). The easitap identical in specification other than the availability of a threaded boss, either tapped or proud on the coupling. Each product has a tolerance designed to accommodate the outside diameters of different pipe materials.



Finish: Black Rilsan Coat
Nuts & Bolts: Rilsan Coat
Gasket: E.P.D.M ("E" Grade)
Options: British Gas LC6 approved gaskets

Product Code	Description	Clamp Size
10450050	Easiclump with Boss (range 66-75mm) - 2"	50mm
10450065	Easiclump with Boss (range 75-84mm) - 2"	65mm
10450080	Easitap with Boss (range 92.3-103mm) - 2"	80mm
10450100	Easitap with Boss (range 115-125.6) - 2"	100mm
10450125	Easitap with Boss (range 141-153.9mm) -2"	125mm
10450150	Easitap with Boss (range 166-181.2mm) .2"	150mm
10450200	Easitap with Boss (range 216.5-226mm) .2"	200mm

EASI CLAMP / EASITAP

A range of high strength repair clamps for use on steel, ductile iron, cast iron PVCu (up to 200mm/8") and PE pipes (up to 220/8"). The easitap identical in specification other than the availability of a threaded boss, either tapped or proud on the coupling. Each product has a tolerance designed to accommodate the outside diameters of different pipe materials.

Finish: Black Rilsan Coat
Nuts & Bolts: Rilsan Coat
Gasket: E.P.D.M ("E" Grade)
Options: British Gas LC6 approved gaskets



Product Code	Description	Clamp Size
10450050	Easiclump with Boss (range 66-75mm) - 2"	50mm
10450065	Easiclump with Boss (range 75-84mm) - 2"	65mm
10450080	Easitap with Boss (range 92.3-103mm) - 2"	80mm
10450100	Easitap with Boss (range 115-125.6) - 2"	100mm
10450125	Easitap with Boss (range 141-153.9mm) -2"	125mm
10450150	Easitap with Boss (range 166-181.2mm) .2"	150mm
10450200	Easitap with Boss (range 216.5-226mm) .2"	200mm

MAXIFIT COUPLING

Couplings Designed to accommodate plain ended pipes with different outside diameters. For use on steel, ductile iron, cast iron, PVCu and asbestos cement.

Finish: Black Rilsan Coat
Nuts & Bolts: Rilsan Coat
Gasket: E.P.D.M ("E" Grade)
Options: British Gas LC6 approved gaskets



Product Code	Description	Clamp Size
10460100	Maxifit Coupling (range 109.6-127.8mm)	100mm
10460101	Maxifit Coupling (range 120-141mm)	100mm
10460125	Maxifit Coupling (range 132.2 146mm)	125mm
10460126	Maxifit Coupling (range 138.9-153.2)	125mm
10460150	Maxifit Coupling (range 159.2-181.6)	150mm
10460200	Maxifit Coupling (range 218.1-235mm)	200mm
10460201	Maxifit Coupling (range 230-247mm)	200mm

MAXISTEP COUPLING

Couplings Designed to accommodate plain ended pipes with different outside diameters. For use on steel, ductile iron, cast iron, PVCu and asbestos cement.

Finish: Black Rilsan Coat
Nuts & Bolts: Rilsan Coat
Gasket: E.P.D.M ("E" Grade)
Options: British Gas LC6 approved gaskets



Product Code	Description	Clamp Size
10470040	Maxistep (range 47.9-59.5 to 72.2/85mm)	40/65mm
10470050	Maxistep (range 59.5-72.2 to 72.2-85mm)	50/65mm
10470051	Maxistep (range 59.5-72.2 to 88.1-102.4mm)	50/80mm
10470081	Maxistep (range 88.1-102.4 to 109.6-127.8mm)	80/100mm
10470100	Maxistep (range 107.2-115 to 109.6-127.8mm)	100mm
10470101	Maxistep (range 109.6-127to8 /118/131.5mm)	100mm
10470102	Maxistep (range 109.6-127.8 to 132.2-146mm)	125mm
10470125	Maxistep (range 132.2-146 to 138.9-153.2mm)	125mm
10470126	Maxistep (range 132.2-146to 159.2-181.6)	125/150mm
10470127	Maxistep (range 138.9-153 to 159.2-181.6)	125/150mm
10470150	Maxistep (range 159.2-181.6 to 171.5-193)	150mm